

FLEXYLED HE CH 3.0



FLEXYLED HE CH 3.0

Domus Line
design

Flexible LED modules with Plug&Play connection system

Materials:

flexible LED strip with adhesive

Covering:

high reflectance paint

Light source:

static light LED module

Number of LEDs:

120 LED/metre



Application type:

universal



Installation:

surface or integrated into the profiles



FLEXYLED HE CH 3.0 is available in rolls of 5 m and 20 m in length. The new CH 3.0 connection system, just 13 mm wide, allows you to incorporate the LED strip into various profiles in this collection. The innovative Plug&Play wiring system is used to create custom lengths without the need for complicated wire welding.



Colour appearance natural white
Colour temperature 4300 Kelvin
Luminous efficiency 85 lm/W
CRI Ra ≥ 80



Colour appearance warm white
Colour temperature 3100 Kelvin
Luminous efficiency 85 lm/W
CRI Ra ≥ 80



Colour appearance super warm white
Colour temperature 2700 Kelvin
Luminous efficiency 85 lm/W
CRI Ra ≥ 80

* values referring to FLEXYLED HE CH 3.0 1000mm

TECHNICAL DATA

Power	9,6W/m
Power supply	24Vdc
LEDs/metre	120
Divisibility	5cm (6 LED)
Protection	IP20
Adhesive 3M®	yes



FLEXYLED HE CH 3.0

rolls of 120 LED/m



Length	Watt & Volt	Light colour	LED
5 metres	48W @ 24Vdc	warm white	600
20 metres	192W @ 24Vdc	warm white	2400

LED CONVERTER AND POWER CABLE NOT INCLUDED. TO BE ORDERED SEPARATELY.

24Vdc

